


FTTP Outdoor Cable with BendBright^{XS} Fibre

Installation in duct

Cable design



-not to scale -

- Tight buffered BendBright^{XS} fibres
- Dielectric longitudinal yarns
- Flame retardant LSOH inner sheath
- Radial dielectric strength members
- PE Outer sheath. Black.

SM@RTCORD

&



BendBright^{XS}
at core

Features and advantages

Installation in duct.

- BendBright^{XS} fibre provides the lowest attenuation at 1550nm and 1625nm after installation.
- The cable is specifically designed for use in the last leg of the Fibre To The Premises (FTTP) applications.
- The cable can be pre-connectorised and protected with QuickDraw^{XS} pulling shroud for ease of installation. Tensile Strength (installation) 600 Nr

Static cable bending radius 60 mm

Temperature range -10°C to +70°C

Technical data

Number of fibres	≤	2
Cable diameter	mm	6 ± 0.3
Cable weight	kg/km	30

International standards

IEC 60794; IEC 60793; ITU-T Rec. G.650; ITU-T Rec. G.657

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.